Prestandadeklaration
Declaration of Performance

Ventilerade läkt/Ventilated battens
FLV, FLVB, FLV45
DoP LP260619



Prestandadeklaration LP260619	
Tillverkare	Lindab Profil AB Vistorpsvägen SE-269 71 Förslöv Tel: 0431-85000, Email: profil@lindab.com
Kontrollerande organ	–
System för bedömning och fortlöpande kontroller	–
Angiven prestanda	SS-EN EN14195
Prestandaegenskaper	Metallkomponenter för gipsskivsystem - Definitioner, krav och provningsmetoder
Prestandaidentifiering	CE-märkning CE - EN14195 finns angivet I förekomna monteringsanvisningar.

Produktinformation	
Produktbeteckning	FLV, FLVB, FLV45
Produktens avsedda användning	Ventilerad läkt
Särskilda anvisningar för användning	Produkten ska vara monterad enligt gällande anvisningar
Dimensionell förändring	
Material:	SUB250GD+PE25, SUB350GD+PE25, SUB350GD+PE25
Tjocklek och klass	0,6; 1,0 mm

Väsentliga egenskaper	Prestanda	Standard
Vattenbeständighet:	NPD (No performance determined)	
Frigörande av farliga ämnen:	NPD (No performance determined)	
Reaktion vid brandpåverkan:	A1	SS-EN EN14195
Brottseghet/slaghållfasthet:	NPD (No performance determined)	

- Denna prestandadeklaration omfattar flera produktvarianter som har samma väsentliga egenskaper och samma deklarerade prestanda. Skillnader mellan produkterna (t.ex. tjocklek, färg) påverkar inte de deklarerade egenskaperna.
- Prestandan för produkten ovan är i överensstämmande med deklarerad prestanda i tabellen ovan.
- Denna prestandadeklaration utfärdas på eget ansvar av Lindab Profil AB undertecknat för tillverkaren av:

Utfärdat av	Utf. datum	Rev. nr	Rev. datum	Språk
Joakim Jönsson Product manager	2026-06-14	1		SV

Declaration of Performance LP260619	
Manufacturer	Lindab Profile AB Vistorpsvägen SE-269 71 Förslöv Tel: 0431-85000, Email: profil@lindab.com
Supervising organisation	–
Assessment and continuous monitoring system	–
Declared performance	SS-EN EN14195
Performance characteristics	Metal components for plasterboard systems – Definitions, requirements and test methods
Performance identification	CE marking (CE – EN 14195) is specified in the installation instructions provided.

Product information	
Product identification	FLV, FLVB, FLV45
Intended use of the product	Ventilated battens
Specific instructions for use	The product must be installed according to the applicable instructions
Dimensional change:	
Material:	SUB250GD+PE25, SUB350GD+PE25, SUB350GD+PE25
Thickness and class	0,6; 1,0 mm

Essential characteristics	Performance	Standard
Water permeability:	NPD (No performance determined)	
Emission of dangerous substances:	NPD (No performance determined)	
Reaction to fire impact:	A1	SS-EN EN14195
Resistance to concentrated force:	NPD (No performance determined)	

- This declaration of performance covers several product variants that have the same essential characteristics and the same declared performance. Differences between the products (e.g. thickness, colour) do not affect the declared characteristics.
- The performance of the product above is in accordance with the declared performance in the table above.
- This declaration of performance is issued on the sole responsibility of Lindab Profil AB signed for the manufacturer by:

Issued by	Date	Rev. nr	Rev. date	Language
Joakim Jönsson Product manager	2026-06-14	1		ENG